

Pipette BLUE

A30-Series

This pipette is general purpose pipette for sampling and dispensing accurate liquid volumes. The pipettes operate on the air displacement principle and use disposable tips. The black tip cone can be sterilized (121 'C, 0.15 Mpa)

The pipette cover a volume range of 0.5ul up to 5,000ul (5ml) All pipettes have been quality tested according to our company's demands. The quality control according to our company's involves gravimetric testing of each pipette with distilled water at 22 'C using the manufacturer's original tips.



Specification

Cat. No.	Volume Range(μl)	Increment (μl)	Test Volume(μl)	Inacc (%)	Impr (%)	Tip
A30-0010	0.5-10 μl	0.1 μl	10 μl	± 3.0	≤ 12.01	10 μl
			5 μl	± 6.0	≤ 13.01	
			1 μl	± 10.0	≤ 13.01	
A30-0020	2-20 μl	0.5 μl	20 μl	± 3.0	≤ 11.51	300 - 350 μl
			10 μl	± 3.0	≤ 12.01	
			2 μl	± 10.0	≤ 13.01	
A30-0100	10-100 μl	1 μl	100 μl	± 1.5	≤ 11.01	300 - 350 μl
			50 μl	± 2.2	≤ 11.51	
			10 μl	± 3.0	≤ 12.01	
A30-0200	20-200 μl	1 μl	200 μl	± 1.5	≤ 11.01	300 - 350 μl
			100 μl	± 1.5	≤ 11.01	
			20 μl	± 3.0	≤ 11.51	
A30-1000	100-1000 μl	5 μl	1000 μl	± 1.2	≤ 10.51	1000 μl
			500 μl	± 1.5	≤ 10.51	
			100 μl	± 1.5	≤ 11.01	
A30-5000	1000-5000 μl	50 μl	5000 μl	± 1.0	≤ 10.51	5000 μl
			2500 μl	± 1.0	≤ 10.51	
			1000 μl	± 1.2	≤ 10.51	

Package

The pipette package contain the following : Pipette, Opening tool, Instruction for use

Package size : 8.0 x 27.8 x 4.1 cm